



HAMMER MILL

TIN2/TIN3



HAMMER MILL

TIN2/TIN3

TIN is a high performance hammer mill for the production of dry grain flours.



- /// Polyethylene hopper with flow regulation
- /// Polyethylene cyclone with two outlets to bag the bran
- /// Direct coupling of the electric motor to the rotor shaft by means of elastic sleeves that reduce vibration and compensate for misalignment
- /// Counterhammer that helps breaking the grains
- /// Comes with 3.2 and 4 mm strips with options from 0.3 to 17 mm
- /// Optional driver channel kit to work together with the Incomagri Mixer MIN

Homogeneous mixture of bran and low inclusion ingredients for the preparation of balanced feed
 *Average production in kg / h. Corn threshed with 13% moisture

TECHNICAL SPECIFICATIONS

Model	Sieve 3,2 mm	Sieve 4 mm	Motor	RPM
TIN-2	1300 kg / 1400 kg	1600 kg / 1700 kg	10 cv / 12,5 cv	3500 / 3500
TIN-3	1700 kg / 2330 kg	1940 kg / 2700 kg	15 cv / 20 cv	3500 / 3500

*Electric motor not included

*Weight and dimensions may vary depending on the product version.
 Project changes may occur without prior notice.

**Merely illustrative images*



Rod. Estadual SP-147, 41 - 13.974-905 - Itapira/SP
 incomagri@incomagri.com.br

(19) 3843-9900

