

Incomagri

HYDRAULIC MOUNTED BOOM SPRAYER

**ATTACK
600AH**



HYDRAULIC MOUNTED BOOM SPRAYER

ATTACK 600AH

The Hidraulic Mounted Boom Sprayer Attack 600 AH is a precise machine, resistant and provides a safe, practical and efficient application. Meets with the needs of the most demanding farmer. Different versions available and a range of optionals that add technology to the equipment, bringing more comfort to the operator and optimizing the spraying task.



Optional:

- /// Pesticides incorporator
- /// Flush tank (clean water for system washing)
- /// Electro-electronic control of the boom and the spraying system
- /// Foam marker
- /// GPS with flow controller
- /// GPS with flow controller and automatic closing section



TECHNICAL SPECIFICATIONS

Model	Attack 600 AH		
Tank	Capacity: 600 l (Made of polyethylene with U.V protection)		
Boom lenght	12/14/16 m		
Boom sytem	Independent hydraulic system Open and close right and left side, up and down the frame Optional: Electrohydraulic		
Working height	0,5 a 1,30 metros		
Nozzles	Trijet with anti-drip valve		
Space between nozzles	50 cm		
Spraying tips	Standart: Flat / Optional: Flat and conical		
Pump	BMIN 85 - Diaphragm pump with cast aluminium housing Flow 85 l/min at 540 rpm Max. Pressure 20 bar		
Spraying manifold valve	2/4 sections or CCP (calibrated return) manual or electric		
Agitator	Hydraulic by return		
Hands Cleaner tank	15 l (Polyethylene)		
Filters	Suction filter (50 mesh) / Line filter (80 mesh) / Nozzle filter (100 mesh)		
Loading	Ecological suction (85l/min) or by gravity		
Weight and dimensions	Attack 600 AH 12m	Attack 600 AH 14m	Attack 600 AH 16m
Lenght (m)	1,6	1,6	1,6
Height (m)	2,8	3,2	2,8
Width (m)	2,2	2,2	3
Weight (kg)	470	480	501

*Weight and dimensions may vary depending on the product version.
Project changes may occur without prior notice.

**Merely illustrative images*



Rod. Estadual SP-147, 41 - 13.974-905 - Itapira/SP
incomagri@incomagri.com.br
(19) 3843-9900

