







Attack Pastus 600 is the the ideal sprayer for applications in pasture areas, its narrow boom with special boomless nozzle produces a wide application that allows to work in difficult access zones for equipment with conventional boom.



Total area application

- Directed manual application
- Reinforced support and reels
- Sturdy chassis
- Polyethylene tank with U.V protection
- Application range from 10 to 11.5m

TECHNICAL SPECIFICATIONS	
Model	Pulverizador Attack Pastus 600
Capacidade tanque reservatório	600 I
Boom lenght	1,9 m
Application range	10 a 11 m
Working height	Recommended target height 0.9m
Manual aplicator kit	2 side reels with 12,5m hose for localized application
Pump	BMIN 85 - Diaphragm pump with cast aluminiun housing Flow 85 I/min at 540 rpm Max. Pressure 20 bar
Spraying manifold valve	3 Sections
Agitator	Hydraulic by return
Hands Cleaner tank	15 l (polyethylene)
Filters	Suction filter (50 mesh) / Line filter (80 mesh) / Nozzle filter (100 mesh)
Loading	Ecological suction (85l/min) or by gravity
Lenght (m)	2,07 m
Height (m)	1,78 m
Width (m)	1,05 m
Weight (kg)	260 m

\*Weight and dimensions may vary depending on the product version. Project changes may occur without prior notice

\*Merely illustrative images



Rod. Estadual SP-147, 41 - 13.974-905 - Itapira/SP incomagri@incomagri.com.br

(19) 3843-9900



## www.incomagri.com.br