







The Hidraulic Mounted Boom Sprayer Attack 800 AH is a precise machine that gives bigger autonomy and provides a safe, practical and efficient application. Meets with the needs of the most demanding farmer. Different versions available and a range of optionals that add technology to the equipment, bringing more comfort to the operator and optimizing the sprayng task.





Opcionais:

- Electric spraying and electro-hydraulic control to activate the boom functions
- Conjugated panel
- GPS with flow controller and automatic closing section
- 🛹 Foam marker



	TECHNIC	AL SPECIFICATIONS			
Model	Attack 800 AH				
Tank	Capacidade de 800 I (Em Polietileno Virgem com proteção U.V)				
Boom lenght	12/14/16/18 m				
Boom sytem	Independent hydraulic system Open and close right and left side, up and down the frame Optional: Electrohydraulic				
Working height	0,5 to 1,30 meters				
Nozzles	Trijet with anti-drip valve				
Space between nozzles	50 cm				
Spraying tips	Standart: Flat / Optional: Flat and conical				
Pump	BMIN 85- Diaphragm pump with cast aluminiun housing Flow 85 l/min at 540 rpm Max. Pressure 20 bar				
Spraying manifold valve		2/4 sections or CCP (calibrated return) manual or electric			
Agitator	Hydraulic by return				
Hands Cleaner tank	15 I (Polyethylene)				
Filters	Suction filter(50 mesh) / Line filter (80 mesh) Nozzle filter (100 mesh)				
Loading		Ecological suction (851/min) or by gravity			
Weight and dimensions	Attack 800 AH 12m	Attack 800 AH 14m	Attack 800 AH 16m	Attack 800 AH 18m	
Lenght (m)	1,5	1,5	1,7	1,7	
Height (m)	2,8	3,2	3,2	3,2	
Width (m)	2,2	2,2	3,05	3,05	
Weight (kg)	470	490	611	627	

*Weight and dimensions may vary depending on the product version. Project changes may occur without prior notice.

*Merely illustrative images



Rod. Estadual SP-147, 41 - 13.974-905 - Itapira/SP incomagri@incomagri.com.br



(19) 3843-9900

www.incomagri.com.br